

Position Indicating Strobe Light for Lifeboat (MED/SOLAS Approved)

Model: DSW9812

Technical Specifications

- **Type Of Light:** Halogen Lamp
- **Output Power:** DC12V, 13W
- **Flash Frequency:** 50-70 times/minute
- **Flash Intensity:** $\geq 4.3\text{cd}$
- **Size:** $\varnothing 102\text{mm} \times 115\text{mm}$
- **Activation Method:** The wire must be manually connected to the power supply equipment on the boat, and the light should be installed on the canopy of the lifeboat to ensure higher visibility.

Certifications

- **Approval:** RINA certificate
- **Testing Standards:** IMO Res. MSC.81 (70), as amended, EN 60945:2002 incl. IEC 60945 Corr.1:2008, ISO 24408:2005
- **Reference Standards:** SOLAS 74 Reg. III/34, IMO Res. MSC.36(63)-(1994 HSC Code) 8, IMO Res.MSC.48(66)-(LSA Code) I, IMO Res. MSC.48(66)-(LSA Code) IV, IMO Res.MSC.97(73)-(2000 HSC Code) 8, IMO MSC.1/Circ.1628
- **Approval:** CCS certificate
- **Approval Standards:** Regulations 4,7,22,26,32 and 34, Chapter III of International Convention for the Safety of Life at Sea, 1974, as amended. Chapter I,II and IV of MSC.48(66) International Life-saving Appliance Code, as amended. Part 1 of MSC.81(70) Revised Recommendation on Testing of Life-saving Appliance, as amended.



Manufacturer



Dongtai Martian Ship Equipment Co., Ltd.



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And
Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.

Mars Safety International Pte Ltd is the Singapore Overseas Branch of Dongtai Martian Ship Equipment Co., Ltd.

No.1 Tuas Link 1, Singapore 638583 Tel.: +65 6862 1212 Fax: +65 6897 9959 For Orders, please send enquiry to Sales@mars-safety.com



Product Features

- MED/SOLAS approved position indicating strobe light for lifeboat, enhances visibility during emergencies, especially in low-light or dark conditions.
- This light is intended for motorised survival craft and to be connected to the crafts 12V electrical system.
- The light should be mounted on the canopy of the lifeboat to enhance visibility.
- The flashing light produces a minimum of 4.3cd in all directions.
- No battery replacement required.



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.