

Self-Igniting Lifebuoy Light Explosion Proof (MED/SOLAS Approved)

Model: HXQD-FB-A IMPA: 330329

Technical Specifications

- **Body Material:** PC, ABS
- **Dimension Of Body:** Ø100mm x 205mm
- **Color Of Lampshade:** Semi-transparent
- **Light Intensity:** ≥2cd
- **Light Duration:** ≥2h over 2cd
- **Explosion-Proof Grade:** Ex ic IIA T4 Gc
- **Bulb Type:** White LED, 3V 0.13A
- **Light Type:** Flashing
- **Flash Frequency:** 50-70 times/minute
- **Battery:** Lithium CR123A (included)
- **Working Voltage:** 3V
- **Battery Validity:** 5 Years
- **Storing Temperature:** -30°C ~ +65°C
- **Working Temperature:** -1°C ~ +30°C
- **Activation Method:** Must be activated first via toggle switch

Certifications

- **Approval:** RINA certificate
- **Testing Standards:** IMO Res. MSC.81 (70), as amended, EN 60945:2002 incl. IEC 60945 Corr.1:2008, ISO 24408:2005
- **Reference Standards:** SOLAS 74 Reg. III/7, SOLAS 74 Reg. III/22, SOLAS 74 Reg. III/32, SOLAS 74 Reg. III/34, IMO Res. MSC.36(63)-(1994 HSC Code) 8, IMO Res. MSC.48(66)-(LSA Code) I, IMO Res. MSC.48(66)-(LSA Code) II, IMO Res. MSC.97(73)-(2000 HSC Code) 8, IMO MSC.1/Circ.1628
- **Approval:** CCS certificate
- **Approval Standards:** Regulations 4,7,22,26,32 and 34, Chapter III of International Convention for the Safety of Life at Sea, 1974, as amended. Chapter I,II and IV of MSC.48(66) International Life-saving Appliance Code, as amended. Part 1 of MSC.81(70) Revised Recommendation on Testing of Life-saving Appliance, as amended.



MARINE SAFETY ESSENTIALS


We Offer On-Board Firefighting And Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.


Mars Safety International Pte Ltd is the Singapore Overseas Branch of Dongtai Martian Ship Equipment Co., Ltd.

No.1 Tuas Link 1, Singapore 638583 Tel.: +65 6862 1212 Fax: +65 6897 9959 For Orders, please send enquiry to Sales@mars-safety.com

Installation Instructions



How To Activate Light



- (1) Install the lifebuoy light clip on the lifebuoy bracket, ensure the light is always placed Upside Down (off state).
- (2) Secure the lifebuoy light to the lifebuoy using the supplied tie string, allowing it to be deployed simultaneously with the lifebuoy.
- (3) Pull the Toggle Switch downwards (on state) before deploying the lifebuoy light. Upon hitting the water and in Upright Position, the LED strobe light turns on automatically.

Important Note: Once the light has been deployed, it must be considered expended and replaced with a new light.

Product Features

- MED/SOLAS approved self-igniting lifebuoy light, enhances visibility and aid in the location of life-saving equipment during emergencies, especially in low-light or dark conditions.
- Intrinsically safe, used for hazardous marine activity applications.
- Constructed to withstand harsh marine environments, including resistance to impact and corrosion.
- Designed to be completely waterproof and to float, maintaining visibility above the water surface.
- Emits bright, flashing light, which is visible from considerable distances.
- Activated via toggle switch, LED strobe light turns on automatically when in upright position.
- Plastic clip for lifebuoy light is included.
- Batteries are included.

Add-On Accessories (Separate Order)



Stainless Steel Clip for
Lifebuoy Light



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And
Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.

Mars Safety International Pte Ltd is the Singapore Overseas Branch of Dongtai Martian Ship Equipment Co., Ltd.

No.1 Tuas Link 1, Singapore 638583 Tel.: +65 6862 1212 Fax: +65 6897 9959 For Orders, please send enquiry to Sales@mars-safety.com