

Fall Preventer Device

Model: HXFPD-6T

Technical Specifications

- **Material:** Polymer polyethylene
- **Safe Working Load:** 6000kg (6T)
- **Linear Density:** 230Ktex
- **Diameter:** 20mm
- **Length:** 1m

Product Features

- A Fall Preventer Device (FPD) can be used to minimise risk of injury or death by providing a secondary alternate load path in the event of failure of the on-load hook or its release mechanism or accidental release of the on-load hook.
- Used during launching and recovery of lifeboats or rescue boats.
- 1 set consist 2 pcs slings, 4 pcs shackles and 1 storage box.

Certifications

- **Approval:** ABS certificate
- **Inspection Standards:** Product batch passed the safe working load test using an electronic hoist scale type OCS-B10, sustaining a required minimum safe working load of 6000kg for a duration of 5 minutes with no deformation found.



Manufacturer



Dongtai Martian Ship Equipment Co., Ltd.



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And
Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.