

Foam Life Jacket with Collar 185N (SOLAS Approved)

Model: HX-III IMPA: 330131

Technical Specifications

- **Cover Material:** Polyester
- **Buoyancy Material:** EPE Foam
- **Buoyancy:** ≥185N
- **Buoyancy Loss:** ≤5% (24h)
- **User Suitability:** Adults of weight ≥43kg and height ≥155cm

Certifications

- **Approval:** CCS certificate
- **Approval Standards:** Regulation 4,7,22 and 34, Chapter III of International Convention for the Safety of Life at Sea, 1974, as amended. Chapter I and II of MSC.48(66) International Life-saving Appliance Code, as amended by MSC.207(81), MSC.218(82) and MSC.368(93). Part 1 and Part 2 of MSC.81(70) Revised Recommendation on Testing of Life-saving Appliance, as amended by MSC.200(80), MSC.226(82), MSC.323(89) and MSC.378(93).



Manufacturer



Dongtai Martian Ship Equipment Co., Ltd.



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And
Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.

Mars Safety International Pte Ltd is the Singapore Overseas Branch of Dongtai Martian Ship Equipment Co., Ltd.

No.1 Tuas Link 1, Singapore 638583 Tel.: +65 6862 1212 Fax: +65 6897 9959 For Orders, please send enquiry to Sales@mars-safety.com



User Suitability: Adults Only, Weight \geq 43kg and Height \geq 155cm

Product Features

- SOLAS approved adult sized EPE foam life jacket.
- Ideal for seamen and passengers onboard vessels.
- Comes with SOLAS reflective tape, neck support, one rescue whistles, buddy line, and grabbing loop.
- Allows for chest and waist fastening.

Add-On Accessories (Separate Order)



Life Jacket Lights
Model: HXYD-GD, HXYD-L-B



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.