

Foldable Radar Reflector

Model: TLF-470A

Technical Specifications

- **Color:** Orange
- **Cross Section:** 40m²
- **Length Of Reflector Edges:** 470mm
- **Echoing Area (Total Angle of at least 280°):** ≥7.5m²
- **Minimum Mounting Height (Above water level):** ≥2m
- **Temperature Range:** -30°C ~ 65°C
- **Weight Of Angle Reflector:** <0.7kg
- **Weight Of Supporting Pole:** <1.1kg
- **Total Weight:** <2kg

Content

Foldable Radar Reflector

- (1) Storage Bag
- (2) Instruction Manual
- (3) Bottom Pole Segment
- (4) Center Pole Segment
- (5) Top Pole Segment
- (6) Angle Reflector



Certifications

- **Approval:** CCS certificate
- **Approval Standards:** Chapter IV of MSC.48(66) International Life-Saving Appliance(LSA) Code, ISO8729-1:2010 (Ships and Marine Technology-Radar Reflectors) Part 1:Passive, IMO MSC.164(78) Revised Performance Standards for Radar Reflectors



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And
Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.

Mars Safety International Pte Ltd is the Singapore Overseas Branch of Dongtai Martian Ship Equipment Co., Ltd.

No.1 Tuas Link 1, Singapore 638583 Tel.: +65 6862 1212 Fax: +65 6897 9959 For Orders, please send enquiry to Sales@mars-safety.com



Product Features

- Designed to alert nearby vessels, especially in poor visibility conditions such as mist, rain, or night time.
- Easy to use, assembled or disassembled, no complicated operation is required.

Important Note: Foldable radar reflector should be mounted above all superstructures and at least 2 meters above the waterline to ensure visibility on the radar screens of large ships and fishing vessels.



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.