

Recovery Strop

Model: HXHSS-1 / HXHSS-2

Lengths Available:

- Ø20mm X 1.5m (HXHSS-1)
- Ø20mm X 1.8m (HXHSS-2)

Technical Specifications

- **Material:** Polymer polyethylene
- **Safe Working Load:** 6500kg (6.5T)
- **Diameter:** 20mm

Product Features

- A Recovery Strop is used for the safe retrieval of lifeboats during drills and emergency recovery operations.
- Prevents injury to crew members connecting the hooks during rough weather caused by the lifeboat's fall blocks.
- 1 set consist 1pc sling, 1pc lifting ring, 1pc shackle and 1 storage box.

Certifications

- **Approval:** ABS certificate
- **Inspection Standards:** Product batch passed the safe working load test using an electronic hoist scale type OCS-B10, sustaining a required minimum safe working load of 6500kg for a duration of 5 minutes with no deformation found.



Manufacturer



Dongtai Martian Ship Equipment Co., Ltd.



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.

Mars Safety International Pte Ltd is the Singapore Overseas Branch of Dongtai Martian Ship Equipment Co., Ltd.

No.1 Tuas Link 1, Singapore 638583 Tel.: +65 6862 1212 Fax: +65 6897 9959 For Orders, please send enquiry to Sales@mars-safety.com