

Lifebuoy (MED/SOLAS Approved)

Model: HX5556 (2.5kg) IMPA: 330159

Model: HX5557 (4.3kg) IMPA: 330160

Technical Specifications

HX5556 (2.5kg)

- **Weight:** $\geq 2.5\text{kg}$
- **Inner Diameter:** $436 \pm 10\text{mm}$
- **Outer Diameter:** $720 \pm 10\text{mm}$

HX5557 (4.3kg)

- **Weight:** $\geq 4.3\text{kg}$
- **Inner Diameter:** $456 \pm 10\text{mm}$
- **Outer Diameter:** $747 \pm 10\text{mm}$

Product Features

- MED/SOLAS approved
- Polyurethane foam buoyancy material.
- Complete with Solas reflective tape and poly rope.

Add-On Accessories (Separate Order)



Lifebuoy Bracket



Life Buoy Quick Release Device



Encapsulated Life Buoy Rescue line

Certifications

- **Approval:** RINA certificate
- **Testing Standards:** IMO Res.MSC 81(70) as amended
- **Reference Standards:** SOLAS 74 Reg.III/7, SOLAS 74 Reg.III/22, SOLAS 74 Reg.III/34, IMO Res.MSC.36(63)-(1994 HSC Code) 8, IMO Res.MSC.48(66)-(LSA Code) I, IMO Res.MSC.48(66)-(LSA Code) II, IMO Res.MSC.97(73)-(2000 HSC Code) 8, IMO MSC.1/Circ.1470. IMO MSC.1/Circ.1628



MARINE SAFETY ESSENTIALS

We Offer On-Board Firefighting And Marine Safety Essentials

Disclaimer: Accuracy of all technical data and information are provided to the best knowledge of the manufacturer. Properties, specifications and application parameters are subject to change without notice. The manufacturer does not undertake any liability of any kind whatsoever.

Mars Safety International Pte Ltd is the Singapore Overseas Branch of Dongtai Martian Ship Equipment Co., Ltd.

No.1 Tuas Link 1, Singapore 638583 Tel.: +65 6862 1212 Fax: +65 6897 9959 For Orders, please send enquiry to Sales@mars-safety.com